



LaboForce-100		
Specimen mover	Specimen holder	
	Max. weight	4 kg (8.8 lbs) incl. specimens
	Force	10-50 N single specimen 30-300 N specimen holder
	Force accuracy	+/-5N up to 50 N, +/-10 N on higher values
	Rotational speed	
	in process	50-150 rpm
	Rotational direction	Counter-clockwise, Clockwise
	Motor	180 W
Software and electronics	Display	TFT colour, 320x240 dts, LED backlight
Features	Methods	Included: 10 Struers Metalog Guide methods. Custom made: 3
Safety standards/directives/legislation		See the Declaration of Conformity/Instruction manual
REACH		For information about REACH, contact your local Struers office.
Operating environment	Surrounding temperature	
	During operation	5-40 °C (41-104 °F)
	Humidity	< 85% RH non-condensing
Compressed air supply	Pressure	6-9.9 bar (87-143 psi)
	Recommended quality	Class-5.6.4, as specified in ISO 8573-1
Power supply	Voltage/frequency	1x24 V
	Power inlet	Connected directly to Labopol
	Power	
	Nominal load	180 W
	Current	
	Nominal	5 A
	Max.	8 A
Current, largest load	4.5 A	



TECHNICAL DATA
LaboForce-100

LaboForce-100		
Dimensions and weight	Width	20.3 cm (8")
	Depth	43.3 cm (17")
	Height	57.4 cm (22.6")
	Height (with open cover)	
	Weight	20.5 kg (45.2 lbs)
Noise level	A-weighted sound emission pressure level at workstations	see the Labopol technical data
Vibration level	Declared vibration emission	N/A

Doc. no.: 16367750_B_en
Date of release: 2024.12.03